



HP Designjet T790 44 2400 نقطة لكل 1200 x طابعة كبيرة الحجم اللون (ملم LAN اتصال الشبكة المحلية 1189 x 841 A0 انش)



العلامة التجارية : HP

عائلة المنتجات : Designjet

رمز المنتج : CR649AB1KBUN

اسم المنتج : T790 44

نقطة لكل انش، ألوان الطباعة: سماوي، الرمادية، أرجواني، 1200 x الحد الأقصى للوضوح: 2400. HP Designjet T790 44. 2400 (ملم)، أنواع وسائط درج الورق: ورق صكوك (841 x 1189 A0: صبغية سوداء بدون لمعان، أصفر. الحد الأقصى لحجم الطباعة نوع واجهة. A0، A1، A2، A3، A4. (A0..A9): تسلسل ISO بوند، ورق صور، الاحجام حسب المنظمة الدولية للتوحيد القياسي استهلاك الطاقة (وضعية الاستعداد): 27 عرض، استهلاك الطاقة (النموذجي): USB: USB Type-A. الشبكة: إيثرنت سريع، موصل استهلاك الطاقة (وضعية التوقف): 0,1 عرض. أنظمة التشغيل المتوافقة: Microsoft Windows 7: 120 عرض، استهلاك الطاقة (وضعية التوقف): 0,1 عرض. أنظمة التشغيل المتوافقة: Ultimate/Professional/Home Premium, Windows Vista Ultimate/Business/Home...

Printing		Power	
Colour *	✓	Power consumption (standby)	27 W
Maximum resolution *	2400 x 1200 DPI	Power consumption (typical)	120 W
Printing colours *	Cyan, Grey, Magenta, Pigment matte black, Yellow	Power consumption (off)	0.1 W
Paper handling		System requirements	
Maximum print size *	A0 (841 x 1189 mm)	Mac compatibility	✓
Paper tray media types *	Bond paper, Photo paper		Microsoft Windows 7
ISO A-series sizes (A0...A9)	A0, A1, A2, A3, A4		Ultimate/Professional/Home Premium, Windows Vista
Media thickness	0.8 mm		Ultimate/Business/Home Premium;
Maximum roll length	91 m	Compatible operating systems	Windows XP (32-bit, 64-bit)
Maximum roll diameter	13.5 cm		Professional/Home, Server 2008
Recommended media weight	60 - 328 g/m ²		(32-bit, 64-bit), Server 2003 (32-bit,
Roll paper	✓		64-bit); Mac OS X v10.5, v10.6;
			Citrix XenApp; Citrix XenServer;
			Linux
Ports & interfaces		Weight & dimensions	
Ethernet interface type	Fast Ethernet	Dimensions (WxDxH)	1770 x 701 x 1050 mm
Ethernet LAN *	✓	Weight	81.6 kg
USB port *	✓	Other features	
USB connector	USB Type-A	Line accuracy	+/- 0.1%
USB 2.0 ports quantity	1	Minimum line width	0.06 mm
RJ-45 ports quantity	1	Ink drop	6 pl (C, G, M, pK); 9 pl (mK, Y)
		Coated paper	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-APR-2025. Prints or copies of Information are only valid on the printed Publication date